

General Product Specifications

Linea Pro 7i Scanners

Power Supply	5V through USB C-Type or Station charger
Compatibility	iPhone 7/8
Power Consumption	Deep sleep -20uA
Barcode Scanner	1D Opticon MDL-1000 Laser 2D Intermec EA30 - Image Sensor 752x480 CMOS, OCR
Bluetooth (optional)	Bluetooth 3.0 compatible - Class 2 - Serial Port Profile (SPP) - iAP
Barcode Type	1D symbologies: JAN/UPC/EAN incl. add on, Codabar/NW-7, Code 11, Code 39, Code 93, Code 128, GS1-128 (EAN-128), GS1 DataBar (RSS), IATA, Industrial 2of5, Interleaved 2of5, ISBN-ISMN-ISSN, Matrix 2of5, MSI/Plessey, S-Code, Telepen, Tri-Optic, UK/Plessey. Postal code: Chinese Post, Korean Postal Authority code. Composite codes, MicroPDF417, PDF417. 1D and 2D symbologies: Code 128, EAN-13, EAN-8, Code 39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5, ITF-6, ITF-14, ISBN, Code 93, UCC/EAN-128, GS1 Databar, Matrix 2 of 5, Code 11, Industrial 2 of 5, Standard 2 of 5, Plessey, MSI-Plessey, PDF417, Data Matrix (ECC200, ECC000, 050, 080, 100, 140), QR Code.
RFID Reader (optional)	MiFARE Mini MiFARE Classic 1K / 4K MiFARE Ultra-Light / Ultra-Light-C MiFARE Plus 2K / 4K ISO / IEC 14443 Type A/B ISO / IEC 15693 MiFARE DESFire JIS X 6319-4 (compatible with FeliCA
LEDs	4 LEDs for battery status
Buttons	Scanning button Battery status button
Battery	2400mAh battery (16,850 Scans over approx. 26hrs of use)
Cables	USB Type-C for device charge and sync
Audio Indicator	Electromagnetic Buzzer
Operating Environment	Operating temperature: 0°C to +40°C Operating humidity: 35 to 85% RH Storage temperature: -5°C to +40°C Storage humidity: 10 to 90% RH
Dimensions	1D scanner 157mm x 77mm x 22mm 2D scanner 142mm x 69mm x 27mm
Weight	160 grams (without iOS Device)
Software Support	SDK for iOS platform
Certifications	CE, FCC, Apple Mfi, RoHS, IP66

