

# VPOS 130 Series

The VPOS 130 series features a flexible and user-friendly design. This versatile Touch Screen is adjustable from 4° to 90° and can be extended to be a more complete POS solution by simply adding optional POS peripherals like an MSR reader.

- Variety of Optional Packages
  - Touch Screen of 15" or 17"
  - Magnetic card reader
  - Flush mount VFD screen
  - Finger print scanner
- Slim and Lightweight
- Exchangeable with VESA Wall Mount



## FEATURES:



1. Tilt angle 4°~90° degree  
Adapt to operation in any environment



4. Hidden cable management



2. MSR / Finger print scanner options



5. Easy to operate OSD buttons



3. VFD customer display unit



6. Internal power adapter design



## SPECIFICATIONS:

| Model Name            | VPOS 135                                                               | VPOS 137                                     |
|-----------------------|------------------------------------------------------------------------|----------------------------------------------|
| Motherboard           | B16                                                                    |                                              |
| LCD / Touch Panel     |                                                                        |                                              |
| LCD Size              | 15" TFT LCD                                                            | 17" TFT LCD                                  |
| Brightness            | 250 cd/m <sup>2</sup>                                                  | 300~380 cd/m <sup>2</sup>                    |
| Resolution            | 1024x768                                                               | 1280x1024                                    |
| Touch Screen          | ELO 5-wire resistive                                                   |                                              |
| Tilt Adjustment       | 4° ~ 90°                                                               |                                              |
| External I / O Ports  |                                                                        |                                              |
| VGA                   | 1                                                                      |                                              |
| DC Jack               | 1                                                                      |                                              |
| OSD Button            | 5 x (left, right, power, menu, select)                                 |                                              |
| USB Port              | 1 x USB 2.0 (Type A), 1 x USB 2.0 (Type B to PC)                       |                                              |
| Serial Port           | 2 x COM (1 x DB-9/F type to PC, 1 x RJ-45 type to VFD)                 |                                              |
| Power                 | Adapter (DC 36W, 12V, 3A)                                              |                                              |
| Control/Indicator     |                                                                        |                                              |
| Power Button          | 1                                                                      |                                              |
| Indicator LED         | 1                                                                      |                                              |
| Peripheral            |                                                                        |                                              |
| MSR / Finger print    | MSR (USB) / Finger print scanner (USB) (Either one module is accepted) |                                              |
| Customer display      | 2 x 20 VFD customer display (COM)                                      |                                              |
| Certificate           |                                                                        |                                              |
| EMC & Safety          | FCC Class A / CE Mark / LVD                                            |                                              |
| Environment           |                                                                        |                                              |
| Operating Temperature | 0°C ~ 40°C ( 32°F ~ 104°F )                                            |                                              |
| Storage Temperature   | -20°C ~ 55°C (-4°F ~ 131°F)                                            |                                              |
| Operating Humidity    | 5% ~ 95% RH non-condensing                                             |                                              |
| Storage Humidity      | 5% ~ 95% RH non-condensing                                             |                                              |
| Dimension (W x D x H) | LCD 90° tilt angle: 365.2 x 217.8 x 338.9 mm                           | LCD 90° tilt angle: 399.2 x 217.8 x 381.5 mm |
| Weight (N.W. / G.W.)  | 4.8kg (10.6lbs)                                                        | 6kg (13.2lbs)                                |
| Mounting              | 100mm x 100mm VESA Standard holes                                      |                                              |

Product specifications subject to change without prior notice.