

H-32

HIGHLIGHTS



Windows Embedded Compact 7
2.8" QVGA touch screen
Bluetooth V2.1 + EDR
WiFi, IEEE 802.11 a/b/g/n
1.5 meter drop proof
USB, OTG
IP 54

H-32

Basic product specifications

OPERATION

CPU: AM3354 ARM Cortex A8, 800 MHz **O/S:** Windows Embedded Compact 7 **SOFTWARE:** Wordpad, Internet Explorer, Active Sync, Opticon scanner application, Upgradeable via integrated microSD card slot **RTC:** Supports year, month, day, hour, minute, second (leap year supported)

MEMORY

NAND FLASH: 256 MB **RAM:** 256 MB mobile DDR2 **EXPANSION:** User accessible MicroSDHC

DISPLAY

TYPE: Transflective QVGA with touch panel, with white LED backlight
SIZE: 2.8", 240 x 320 pixels **MODE:** Portrait

OPERATING INDICATORS

VISUAL: 2 LEDs (red/green scanning indication & charging indicator)
NON-VISUAL: Vibrate, Speaker

OPERATING KEYS

ENTRY OPTIONS: 26 keys total, 12 key (alpha)numeric keypad, 4-way navigation keys, function key, backspace key, power key, Enter key, Alpha key, Escape key, Shift key, 3 scan keys,

COMMUNICATION

USB: Micro USB OTG, ver. 2.0 **BLUETOOTH:** Ver. 2.1 + EDR **W-LAN:** 802.11 a/b/g/n; WEP, WPA, WPA2; WEP, TKIP, AES; Static (40 and 128 bit), PSK (Pre-Shared), Dynamic; EAP, PEAP, LEAP; Cisco CCX version 4 **AUDIO:** Speaker
EXTENSION: User accessible microSD I/O

POWER

RECHARGEABLE BATTERY: Lithium-Ion 3.7V 1800mAh (sold separately)
BACKUP BATTERY: fixed rechargeable Lithium-Ion 15mAh **CHARGING METHOD:** Through Micro USB cable (enclosed item) or cradle (sold separately)

BARCODE SCANNER OPTICS

LIGHT SOURCE: 650 nm visible laser diode **SCAN RATE:** 100 scans/sec
READING PITCH ANGLE: -35 to 0°, 0 to +35° **READING SKEW ANGLE:** -50° to -8°, +8° to +50° **READING TILT ANGLE:** -20° to 0°, 0° to +20°
CURVATURE: R>15 (EAN8), R>20 (EAN13) **MIN. PCS VALUE:** 0.45 **DEPTH OF FIELD:** At PCS 0.9, Code 39, 70 - 650 mm / 2.76 - 25.59 in (1.00 mm / 39 mil), 50 - 420 mm / 1.97 - 16.54 in (0.5 mm / 20 mil), 50 - 260 mm / 1.97 - 10.24 in (0.25 mm / 10 mil), 50 - 150 mm / 1.97 - 5.91 in (0.15 mm / 6 mil), 60 - 120 mm / 2.36 - 4.72 in (0.127 / 5 mil)

SUPPORTED SYMBOLOGIES

BARCODE (1D): JAN/UPC/EAN incl. add on, Codabar/NW-7, Code 11, Code 39, Code 93, Code 128, GS1-128 (EAN-128), GS1 DataBar (RSS), IATA, ISBN, Industrial 2of5, Interleaved 2of5, Matrix 2of5, MSI/Plessey, Telepen **POSTAL CODE:** Chinese Post, Korean Postal Authority code **2D CODE:** Composite Codes, MicroPDF417, PDF417

DURABILITY

TEMPERATURE IN OPERATION: -10 to 50°C / 14 to 122°F **TEMPERATURE IN STORAGE:** -20 to 60°C / -4 to 140°F **HUMIDITY IN OPERATION:** 20% to 80% RH **HUMIDITY IN STORAGE:** 20% to 90% RH **DROP TEST:** 1.5 m / 5 ft drop onto concrete surface **PROTECTION RATE:** IP 54

PHYSICAL

DIMENSIONS (W x H x D): 64.8 x 145.7 x 26.8 mm / 2.55 x 5.74 x 1.06 in
WEIGHT BODY: Ca. 195 g / 6.9 oz (incl. battery) **CASE:** Black

REGULATORY & SAFETY

PRODUCT COMPLIANCE: CE, FCC, RoHS, IEC 60825-1 Class 2, FDA CDRH Class II

ENCLOSED ITEMS

USB cable, Handstrap, Quick start guide, Stylus + cord

SOLD SEPARATELY

RECHARGEABLE BATTERY: 3.7V 1800mAh **CRD-32:** Single USB/RS232 cradle, communication, charging **CRD-32-E5:** Multi-cradle, 5 slots, Ethernet communication, charging **HOLSTER**

Authorised Australian & New Zealand Distributor:
Goodson Imports Pty Ltd
9 Liberty Road
Huntingwood NSW 2148
Representation in all main States and New Zealand
Ph: 02-8875 4544 Fax 02-8875 4588
www.goodson.com.au

